




BOSCH

Climate 5000 L • Climate 5000i U/L

CL5000L 35 E • CL5000iU D 35 E | CL5000L 53 E • CL5000iU D 53 E |
CL5000L 70 E • CL5000iU D 70 E | CL5000L 88 E • CL5000iL D 88 E |
CL5000L 105 E • CL5000iL D 105 E | CL5000L 105 E-3 • CL5000iL D 105 E |
CL5000L 125 E • CL5000iL D 125 E | CL5000L 140 E-3 • CL5000iL D 140 E |
CL5000L 160 E-3 • CL5000iL D 160 E

bg	Голям климатичен уред сплит система	Ръководство за обслужване за потребителя	2
de	Large-Split-Klimagerät	Bedienungsanleitung für den Betreiber	14
el	Κλιματιστικό τύπου Split Large	Οδηγίες χρήσης για τον υπεύθυνο λειτουργίας	24
en	Large split air conditioner	Operating instructions for users	36
es	Climatizador Large Split	Manual de servicio para el usuario	46
fr	Climatiseur large split	Notice d'utilisation destinée à l'exploitant	58
it	Condizionatore Large Split	Istruzioni per l'uso per il gestore	69
nl	Large-Split-airconditioning	Gebruiksaanwijzing voor de exploitant	80
pl	Urządzenie klimatyzacyjne large split	Instrukcja obsługi dla użytkownika	90
pt	Ar condicionado split	Manual de instruções para o operador	102
ro	Aparat de aer condiționat de tip split Large	Instrucțiuni de utilizare destinate utilizatorului	113
sq	Kondicioner Large Split	Manuali i përdorimit	124
tr	4 Yöne Üflemeli Kaset Tipi Split Klima	Kullanıcılara Yönelik Kullanma Kılavuzu	134
uk	Спліт кондиціонер для застосування у приміщеннях великих площ	Інструкція з експлуатації для користувача	144



0010040403-001



Table of contents

1	Explanation of symbols and safety instructions	36
1.1	Explanation of symbols	36
1.2	General safety instructions	37
1.3	Notices regarding these instructions	38
2	Product Information	38
2.1	Declaration of conformity	38
2.2	Technical data wired room controller	38
2.3	Specifications of remote control	38
2.4	Operating temperature range	38
2.5	Information on refrigerant	38
3	Operation	39
3.1	Indoor unit overview	39
3.2	Indoor unit display	39
3.3	Overview wired room controllers	39
3.4	Remote control overview	39
3.4.1	Using the remote control	40
3.5	Setting the day and time	40
3.6	Setting main operating mode	40
3.7	Setting the room temperature	41
3.8	Setting timer	41
3.8.1	One-time ON/OFF timer	41
3.8.2	Weekly ON/OFF timer	41
3.8.3	Weekly event timer	41
3.8.4	Additional settings for weekly timer	42
3.9	Other functions	42
3.9.1	Switching the key sound on/off	42
3.9.2	Turbo cool/Turbo heat	42
3.9.3	Noise reduction (Silent Mode)	42
3.9.4	Self-cleaning (I clean)	42
3.9.5	Sleep mode	42
3.9.6	Wireless control function	42
3.9.7	Keylock	42
3.9.8	Follow me function (Follow Me)	42
3.9.9	Setting the Rotation and Back-up function	43
4	Maintenance	43
4.1	Replacing the batteries	43
4.2	Cleaning	43
4.3	Cleaning the air filter	43
4.4	When re-commissioning after decommissioning for an extended period	43
4.4.1	Maintenance before decommissioning for an extended period	43
4.4.2	Maintenance after a long period of non-use	43
5	Troubleshooting	44
5.1	Faults with indication (Self diagnosis function)	44
5.2	Faults not indicated	44
6	Environmental protection and disposal	45
7	Data Protection Notice	45

1 Explanation of symbols and safety instructions

1.1 Explanation of symbols

Warnings

In warnings, signal words at the beginning of a warning are used to indicate the type and seriousness of the ensuing risk if measures for minimizing danger are not taken.

The following signal words are defined and can be used in this document:



DANGER indicates that severe or life-threatening personal injury will occur.



WARNING indicates that severe to life-threatening personal injury may occur.



CAUTION indicates that minor to medium personal injury may occur.

NOTICE

NOTICE indicates that material damage may occur.

Important information



The info symbol indicates important information where there is no risk to people or property.

Symbol	Meaning
	Warning regarding flammable substances: the refrigerant R32 used in this product is a gas with low combustibility and low toxicity (A2L or A2).
	Wear protective gloves during installation and maintenance work.
	Maintenance by a qualified person should be done while following the instructions of the service manual.
	For operation follow the instructions of the user manual.

Table 1

1.2 General safety instructions

Notices for the target group

These operating instructions are intended for the operator of the air conditioning system. All system-relevant instructions must be observed. Failure to comply with instructions may result in material damage and personal injury, including danger to life.

- ▶ Read and retain the operating instructions of all system components prior to use.
- ▶ Observe the safety instructions and warnings.

Intended use

The indoor unit is intended for installation inside the building with connection to an outdoor unit and further system components, e.g. controls.

The outdoor unit is intended for installation outside the building with connection to an indoor unit or units and further system components, e.g. controls.

Any other use is considered inappropriate. Any damage that may result from misuse is excluded from liability.

For installation at special locations (underground garage, mechanical rooms, balcony or at any semi-open areas):

- ▶ First refer to the requirements for the installation site in the technical documentation.

General dangers posed by the refrigerant

- ▶ This appliance is filled with refrigerant. If the refrigerant gas gets into contact with fire, it may generate toxic gas.
- ▶ Have the system inspected and serviced regularly by an approved contractor.
- ▶ If there is a possibility that refrigerant has escaped, thoroughly ventilate the room and notify the approved contractor.

Conversion and repairs

If modifications to the air conditioning system are not carried out correctly, this can result in personal injury and/or material damage.

- ▶ Have work carried out only by an approved contractor.
- ▶ Do not make any changes to the outdoor unit, indoor unit or other parts of the air conditioning system.
- ▶ Disconnect the air conditioning system from the power supply before carrying out any maintenance work.

Notices on handling the system

If the air conditioning system is used incorrectly, this could impair your health.

- ▶ Do not stand directly in the airflow for any length of time.
- ▶ Ensure that the room temperature is suitable for all people in the room, including babies, children, elderly, bedridden or disabled people.
- ▶ Never insert objects into the unit, you could injure yourself.

If the unit is handled incorrectly, this can lead to reduced performance and also damage to the unit and personal injury.

- ▶ Do not block the air inlets and outlets of the unit.
- ▶ Shut doors and windows when the unit is in operation.
- ▶ Protect the indoor unit from water ingress.
- ▶ Check the outdoor unit mounting rack periodically for wear and to make sure it is firmly in place.
- ▶ Do not apply any weight to the outdoor unit, e.g. objects or persons.
- ▶ Keep dust, steam and moisture in the installation room of the indoor unit to a minimum.
- ▶ Do not use highly-flammable gases, e.g. from spray cans, in the vicinity of the units.
- ▶ If there appears to be something wrong with the air conditioner (burning smell or faulty cable for example), stop using it immediately and disconnect the power supply.

Safety of electrical devices for domestic use and similar purposes

The following requirements apply in accordance with EN 60335-1 in order to prevent hazards from occurring when using electrical appliances:

“This appliance can be used by children of 8 years and older, as well as by people with reduced physical, sensory or mental capabilities or lacking in experience and knowledge, if they are supervised and have been given instruction in the safe use of the appliance and understand the resulting dangers. Children shall not play with the appliance. Cleaning and user maintenance must not be performed by children without supervision.”

“If the power cable is damaged, it must be replaced by the manufacturer, its customer service department or a similarly qualified person, so that risks are avoided.”

1.3 Notices regarding these instructions

The figures are shown together at the end of these instructions. The text contains references to the figures.

Depending on the model, the products may be different to those shown in these instructions.

2 Product Information

2.1 Declaration of conformity

The design and operating characteristics of this product comply with the European and national requirements.

 The CE marking declares that the product complies with all the applicable EU legislation, which is stipulated by attaching this marking.

The complete text of the Declaration of Conformity is available on the Internet: worcester-bosch.co.uk.

2.2 Technical data wired room controller

Power infeed	DC 12V
Permissible ambient temperature	-5 °C... 43 °C
Permissible relative humidity	40...90 %

Table 2 Technical data wired room controller

2.5 Information on refrigerant

This device **contains fluorinated greenhouse gases** as refrigerant. The unit is hermetically sealed. The following information on the refrigerant complies with the requirements of EU Regulation No. 517/2014 on fluorinated greenhouse gases.

Product type	Rated cooling output [kW]	Rated heating output [kW]	Refrigerant Type	Global warming potential (GWP) [kg CO ₂ equ.]	CO ₂ equivalent of initial charge	Initial charge volume [kg]	Additional fill volume for pipe length L ¹⁾ [g/m]	Total charge volume during commissioning [kg]
CL5000L 35 E	3.52	3.81	R32	675	0.49	0.72	12	
CL5000L 53 E	5.28	5.57	R32	675	0.78	1.15	12	
CL5000L 70 E	7.03	7.62	R32	675	1.01	1.5	12	
CL5000L 88 E	8.79	9.38	R32	675	1.35	2.0	24	
CL5000L 105 E	10.55	11.72	R32	675	1.62	2.4	24	
CL5000L 105 E-3	10.55	11.72	R32	675	1.62	2.4	24	
CL5000L 125 E	12.02	13.48	R32	675	1.89	2.8	24	
CL5000L 140 E-3	14.07	16.12	R32	675	1.96	2.9	24	
CL5000L 160 E-3	15.24	18.17	R32	675	2.03	3.0	24	

1) Total pipe length L in metres (if L > 5 m simple path from outdoor unit to indoor unit).

Table 5 F-Gas

2.3 Specifications of remote control

Power infeed	2 AAA batteries
Signal range	8 m
Permissible ambient temperature	16... 30 °C

Table 3 Specifications of remote control

2.4 Operating temperature range

	Room temperature	Outside temperature
Cooling	16 ... 32 °C	-15... 50 °C
Heating	0 ... 30 °C	-15... 24 °C
Dehumidifying	10... 32 °C	0... 50 °C

Table 4



The built-in protection device may prevent the appliance from operating at temperatures outside the above range.



If the humidity is more than 80 %, condensation may form at the air outlet. To prevent this, open the vertical ventilation flaps as wide as possible (vertical relative to the ground) and set a high fan output.



Notice for the user: If your installer adds refrigerant, he enters the added fill volume and the total amount of the refrigerant in the following table.

3 Operation

3.1 Indoor unit overview

Key to Fig. 1:

- [1] Air inlet
- [2] Electric control box
- [3] Air filter
- [4] Air Outlet

3.2 Indoor unit display

Key to Fig. 3:

- [1] Manual operation
- [2] Status indicator
- [3] Timer indicator
- [4] Pre-heating and defrosting indicator
- [5] Alarm indicator
- [6] Infrared signal receiver
- [7] LED indicator



The operating modes can be selected in the sequence **automatic mode**, **cooling mode** and **shutdown** via the Manual operation key.

Manual button

Operating Mode	Display	Display output
Automatic mode	Operation indicator on	Cooling and heating modes: Set temperature Fan only mode: Indoor ambient temperature
Manual cooling mode	Status indicator flashes	The system automatically switches to automatic mode after 30 minutes of forced cooling. The remote control is deactivated during forced cooling.
Shutting-down	All indicators off	If the display is switched off, the indoor unit switches off and the remote control is reactivated.

Table 6 Indications on the display unit

3.3 Overview wired room controllers

Keys of the wired room controller

Key to figure 3:

- [1] Receiver for infrared remote control
- [2] Display of the wired room controller
- [3] Keys of the wired room controller

Key	Function
	Switch on/off.
M	Set operating mode.
DAYOFF	Day off/deletion.
^ v	Adjust up/down setting.
	Confirm choice.
TIMER	Set timer.
	Fan step
	Navigate back.
	No function.
FUNC.	Set function.
COPY	Copy/adopt data.

Table 7 Keys of the wired room controller

Display of the wired room controller

Key to figure 4:

- [1] Display of main operating modes
- [2] Display of temperature and status
- [3] Display time
- [4] Timer display

Pos.	Symbol	Explanation
1	Display of main operating modes	
		Operating mode: automatic mode
		Operating mode: cooling mode
		Operating mode: dehumidification mode
		Operating mode: heating mode
		Operating mode: Fan Mode
		Operating mode: On/Off
2	Display of temperature and status	
		Value display: shows the current fan speed. There are several output stages (bars) and the AUTO setting for automatic control
		Value display: indicates the set temperature as standard.
		Infographic: keylock
		Infographic: appliance 1/2
		Infographic: Turbo cool/Turbo heat is active.
		Infographic: room temperature
		Infographic: automatic rotation is active.
	Infographic: Follow me active.	
3	Time display	
		Value display: indicates time.
4	Timer display	
		Infographic: timer On/Off
		Infographic: weekdays active
		Infographic: day
		Infographic: week

Table 8 Symbols in the display

3.4 Remote control overview

Keys on remote control

→ Fig. 5

Pos.	Key	Function
1		Switch on/off.
	Mode	Set operating mode.
		Eco operation mode
2	SET	Select advanced operating functions.
	OK	Confirm choice.
		Set timer.
	^	Increase temperature.
	v	Reduce temperature.
3		Fan step
		Indirect airflow is active (Wind avoid me).
	Turbo	Turbo cool/Turbo heat
	LED	Switch display of indoor unit and alarm buzzer on and off (Mute Mode).
	Clean	Self-cleaning (I clean)

Table 9 Keys on remote control

Display of remote control

→ Fig. 6

Pos.	Symbol	Explanation
1		Operating function: Sleep mode is active.
		Operating function: Follow Me function is active (Follow Me); temperature measurement at the remote control.
		Infographic: wireless control function
		Infographic: battery status
2		Operating mode: automatic mode
		Operating mode: cooling mode
		Operating mode: dehumidification mode
		Operating mode: heating mode
		Operating mode: Fan Mode
3		Value display: shows the set temperature, fan speed or (when timer is activated) the timer setting as standard.
		Infographic: transmission indicator; lights up when the remote control sends a signal to the indoor unit.
		Infographic: energy saving function active.
		Infographic: energy saving function active.
		Infographic: ON/OFF timer active.
		Infographic: noise reduction is active (Silent Mode).
		Value display: shows the current fan speed. There are several output stages (bars) and the AUTO setting for automatic control
4		Infographic: Turbo cool/Turbo heat is active.

Table 10 Symbols in the display

3.4.1 Using the remote control

The signal range is 8 m. If objects are in the way or certain fluorescent lamps are used in the same room this can affect transmission of the signal.

- ▶ Point the remote control towards the signal receiver window of the unit and press the desired key.
The unit emits a beep when it receives a signal.

NOTICE

The remote control may be permanently prevented from working correctly.

- ▶ Do not expose the remote control to direct sunlight.
- ▶ Do not leave the remote control near a heating appliance.
- ▶ Protect the remote control from moisture and impacts.

3.5 Setting the day and time

- ▶ Press the **TIMER** key until the timer display starts flashing.
- ▶ Select the current day with the \wedge and \vee keys. The selected day flashes.
- ▶ Press the **TIMER** or \square key to confirm the entry.
The selection jumps to the time.
- ▶ Press or hold the \wedge or \vee key to set the time.
- ▶ Press the **TIMER** or \square key to confirm the entry.

To toggle between 12- and 24-hour display:

- ▶ Press/keep the **TIMER** and **DAY OFF** keys pressed simultaneously for several seconds.

3.6 Setting main operating mode

Depending on the indoor unit and configuration of the wired room controller, not all operating modes may be available.

Turn unit on/off

- ▶ Press the \odot key to switch the device on or off:
The unit starts in the set operating mode or switches off. To protect the unit it can only be switched back on after some time has passed.

Settings can also be made when the appliance is switched off. The device saves the settings, and also retains them in the event of a power failure.



After it has been switched off, the unit remains in standby mode. An automatic energy saving mode is enabled in standby mode due to intelligent On/Off technology (1 W standby).



Following a power failure the unit restarts automatically. This can lead to conflicting readings on the displays which are resolved automatically during operation.

Automatic mode

In automatic mode, the unit switches automatically between heating, cooling, fan and dehumidification mode, depending on the set temperature.

- ▶ Press the **M** key repeatedly until \odot appears on the display.
- ▶ Press the \wedge or \vee key to set the required temperature.



The fan speed cannot be adjusted in automatic mode.

Cooling mode

- ▶ Press the **M** key repeatedly until \ast appears on the display.
- ▶ Press the fan key until the required air speed is reached.
- ▶ Press the \wedge or \vee key to set the required temperature.

Dehumidification mode

- ▶ Press the **M** key repeatedly until water appears on the display.
- ▶ Press the \wedge or \vee key to set the required temperature.



The fan speed cannot be adjusted in dehumidification mode.

Heating mode

- ▶ Press the **M** key until sun appears on the display.
- ▶ Press the \wedge or \vee key to set the required temperature.
- ▶ Press the fan key until the required air speed is reached.



If the outside temperature is very low, the heating capacity of the air conditioning system may not be sufficient. We recommend connecting additional heat sources.

Fan (Only) Mode

- ▶ Press the **M** key repeatedly until fan appears on the display.
- ▶ Press the fan key until the required fan speed is reached. **AUTO** can be selected to enable automatic control.

 The temperature cannot be adjusted or displayed in fan mode.

3.7 Setting the room temperature

- ▶ Press the **^** or **v** key to set the desired room temperature. The setting is applied shortly afterwards.

 The temperature cannot be adjusted in Fan Mode.

3.8 Setting timer

3.8.1 One-time ON/OFF timer

- ▶ Press the **TIMER** key repeatedly until the corresponding symbol appears.
 - ON timer: **ON DAY**
 - OFF timer: **OFF DAY**
 - ON and OFF timer: **ON+OFF DAY**
- ▶ Confirm with  key. The clock display starts flashing.
- ▶ Press the **^** or **v** key to set the desired ON/OFF time.
- ▶ Press the  key again to save the setting.

 The ON/OFF timer cannot be set at a secondary wired room controller.

3.8.2 Weekly ON/OFF timer

Setting timer

- ▶ Press the **TIMER** key until **WEEK 1** appears in the display.
- ▶ Confirm with  key.
- ▶ Press the **^** or **v** key to select the weekday.
- ▶ Confirm with  key.
- ▶ Press the **^** or **v** key to set the desired ON time.
- ▶ Confirm with  key.
- ▶ Press the **^** or **v** key to set the desired OFF time.
- ▶ Confirm with  key.

 Up to four times can be set.

- ▶ Repeat procedure every subsequent day of the week.

To delete the timer for the selected day:

- ▶ Press the **DAY OFF** key.

Activating the timer

- ▶ Keep pressing the **TIMER** key until **WEEK 1** appears in the display. The timer is now switched on. The unit is switched on or off at the selected times and days.

Deactivating the timer

- ▶ Keep pressing the **TIMER** key until **WEEK 1** disappears in the display. To switch off the unit when the week timer is active:
 - ▶ Briefly press  key. The unit switches off until the next ON timer is reached.
 - ▶ Hold the  key pressed for two seconds to switch off the unit and deactivate the week timer.

Programming the switch-on delay

If week timer 1 is active and the ON time is to be delayed.

- ▶ Select week timer 1 with **TIMER** key.
- ▶ Press the **DAY OFF** key 2x until 1h appears on the display.
- ▶ Wait for a few seconds while the setting is saved. The unit now starts the next activity cycle following a delay of 1 hour.
- ▶ Press the **DAY OFF** key 3x until 2h appears on the display. The unit now starts the next activity cycle following a delay of 2 hours.

3.8.3 Weekly event timer

Setting timer

 Up to 8 events can be set for each day to change the operating mode, temperature and fan speed.

- ▶ Keep pressing the **TIMER** key until **WEEK 2** appears in the display.
- ▶ Confirm with  key.
- ▶ Press the **^** or **v** key to select the weekday.
- ▶ Confirm with  key.
- ▶ Press the **^** or **v** key to select the setting time, main operating mode, temperature or fan speed for the event.
- ▶ Confirm with  key.
- ▶ Make the setting and press the  key to confirm or the **DAY OFF** key to delete the setting.
- ▶ Repeat the procedure to define additional setting periods for this day.
- ▶ Follow the same procedure to program additional weekdays.

To delete the timer for the selected day:

- ▶ Press the **DAY OFF** key.

Defining the setting time

- ▶ Press the **^** or **v** key to adjust the time.
- ▶ Confirm with  key.

Selecting the main operating mode

- ▶ Press the **^** or **v** key to select the main operating mode (→ Table 8, [1], page 39).
- ▶ Confirm with  key.

 The fan speed cannot be adjusted in automatic and dehumidification mode.

Setting the room temperature

- ▶ Press the **^** or **v** key to set the desired room temperature.
- ▶ Confirm with  key.

Fan step

- ▶ Press the **^** or **v** key to adjust the fan step.
- ▶ Confirm with  key.

 The temperature cannot be adjusted in Fan Mode.

Activating the timer

- ▶ Press the **TIMER** key until **WEEK 2** appears in the display. The timer is now switched on. The unit will adjust itself automatically on these selected times and days.

Deactivating the timer

- ▶ Press the  or **TIMER** key for several seconds.

3.8.4 Additional settings for weekly timer

Provisionally disabling the timer

To disable the timer on selected days only:

- ▶ Press the **TIMER** key until **WEEK 1** or **WEEK 2** appears in the display.
- ▶ Press the  key.
- ▶ Press the  or  key to select the weekday.
- ▶ Press the **DAY OFF** key.
The selected day is no longer displayed.



The timer is deactivated for the days that are not displayed until the day has passed.

- ▶ Press the **DAY OFF** key again to display the day once again.
- ▶ Repeat the above if necessary for the other days.

Adopting (copying) settings from one day to another day

- ▶ Press the **TIMER** key until **WEEK 1** or **WEEK 2** appears in the display.
- ▶ Press the  key.
- ▶ Press the  or  key to select the day whose settings should be adopted.
- ▶ Press the **COPY** key to copy the settings.
CY appears on the display.
- ▶ Press the  or  key to select the day to which the settings should be copied.
- ▶ Press the **COPY** key to insert the copied settings.
The selected weekday flashes briefly as confirmation.
- ▶ Repeat the above steps if necessary to copy the information to other days.
- ▶ Press the  key to adopt the changes.

3.9 Other functions

3.9.1 Switching the key sound on/off

To switch the the key sound of the wired room controller on or off:

- ▶ Press and hold the  and **FUNC.** keys for three seconds.

3.9.2 Turbo cool/Turbo heat

When Turbo cool/Turbo heat is active, the indoor unit operates at maximum power to heat or cool the room quickly.

Turbo Cool:

- ▶ Switch on cooling mode.
- ▶ Press the **FUNC.** key.
- ▶ Confirm with  key.

Turbo Heat:

- ▶ Switch on heating mode.
- ▶ Press the **FUNC.** key.
- ▶ Confirm with  key.

Exiting the function:

- ▶ Press the **FUNC.** key again.
- ▶ Confirm with  key.

3.9.3 Noise reduction (Silent Mode)

This function reduces the noises emitted by the indoor and outdoor unit when it is in operation. This is particularly advantageous at night, if you need to show consideration for your neighbours.

- ▶ During operation, press the  key for 2 seconds.

Exiting the function:

- ▶ Press the  key again for 2 seconds.

-or-

- ▶ Press the  key, **Mode** key, **Turbo** key or **Clean** key.



When the outdoor unit is in quiet mode, it may not be possible to achieve the required cooling/heating capacity because the compressor operates at a low frequency.

3.9.4 Self-cleaning (I clean)

The device has a self-cleaning function for the evaporator. The self-cleaning freezes dust, mould and grease. Everything is then quickly defrosted and dried with hot air.

- ▶ To activate the self-cleaning: press the **Clean** key.
CL appears on the display of the indoor unit when self-cleaning is in progress. Self-cleaning ends automatically after 20 to 45 minutes.

3.9.5 Sleep mode

The purpose of this function is to save energy during idle times. After an hour, the device heats or cools less intensely. To do this, the set temperature is changed by 1 °C. After two hours, the set temperature changes by a further 1 °C. Then it remains at the new temperature.



The function is not available in dehumidification mode and Fan Mode.

3.9.6 Wireless control function

The purpose of this function is to establish a connection via WLAN.



To connect to WLAN an IP-Gateway (optional accessory) must be installed.

NOTICE

For TWIN installation, an IP gateway is sufficient for the master unit. No gateway is required for the slave unit.

3.9.7 Keylock

The keys of the wired room controller can be locked with the keylock.

To switch the keylock on or off:

- ▶ Press/keep the **TIMER** and **COPY** keys pressed simultaneously for three seconds.
The symbol  appears in the display when the keylock is active.

3.9.8 Follow me function (Follow Me)

This function activates the temperature sensor of the wired room controller. The room temperature is measured at the position of the wired room controller instead of at the indoor unit.

- ▶ Switch off heating or cooling mode if required.
- ▶ Press the **FUNC.** key to switch the function on or off.
When the function is active the wired room unit displays the  symbol.
- ▶ Confirm with  key.

3.9.9 Setting the Rotation and Back-up function



The Rotation function can only be activated if two indoor units are connected to one wired room controller (Twin installation). The Rotation function switches indoor units on or off alternately.

- ▶ Press the **FUNC.** key repeatedly until the  symbol appears.
 - ▶ Press the  key to switch on the Rotation function.
 - ▶ Press the  or  key to set the period that must elapse (0 - 99 hours) before the indoor units rotate.
Default setting: the indoor units rotate every 10 hours.
 - ▶ Confirm with  key.
 - ▶ Press the  or  key to set the maximum temperature:
 - 26... 32 °C: once the set temperature has been reached, both appliances are switched on in cooling mode. The Rotation function is interrupted until 24 °C has been reached.
 - --: no maximum temperature to interrupt the Rotation function.
 - ▶ Confirm with  key.
 - ▶ Press the  or  key to adjust the lowest temperature.
 - 5... 15 °C: once the set temperature has been reached, both appliances are switched on in heating mode. The Rotation function is interrupted until 24 °C has been reached.
 - --: no lowest temperature to interrupt the Rotation function.
 - ▶ Confirm with  key.
 - ▶ Define which indoor unit switches on first (A or B).
 - ▶ Confirm with  key.
- While the Rotation function is active, the indoor units operate alternately, starting with indoor unit A or B.

To change the indoor unit early:

- ▶ Press the  key.



If an indoor unit drops out, the respective **A/B** symbol flashes in the display. The other indoor unit automatically takes over the operation.

4 Maintenance



CAUTION

Danger due to electric shock or moving parts

- ▶ Disconnect the power supply before carrying out any maintenance work.
- ▶ Have any maintenance steps that are not listed here carried out by an approved contractor.

4.1 Replacing the batteries

You require 2 size AAA batteries. Using rechargeable batteries is not recommended.

- ▶ Remove the battery cover (→ Fig. 7).
- ▶ Insert new batteries, ensuring correct polarity.
- ▶ Reinstall the cover.

4.2 Cleaning

NOTICE

Damage to device due to incorrect cleaning!

- ▶ Do not directly splash or pour water onto them.
- ▶ Do not use hot water, thinner, abrasive powders or strong solvents.
- ▶ Clean indoor unit and control unit by wiping them with a soft cloth.
- ▶ Only have the outdoor unit cleaned by a qualified person.

4.3 Cleaning the air filter

NOTICE

The air filter may deform in direct sunlight.

- ▶ Do not expose the air filter to direct sunlight.

Check the air filter every 2 weeks and clean if necessary. Always clean before and after decommissioning for longer periods.

- ▶ Switch off the indoor unit.
- ▶ Pull out the air filter (→ Fig. 8).
- ▶ Wash the air filter with hot water and a mild cleaning agent and dry in the shade.

4.4 When re-commissioning after decommissioning for an extended period

4.4.1 Maintenance before decommissioning for an extended period:

- ▶ Clean the air filter of the indoor unit.
- ▶ Leave the fan of the indoor unit running for approx. 24 h in Fan Mode to allow the inside of the appliance to dry.
- ▶ Switch off the indoor unit and disconnect it from the power supply.
- ▶ Protect the devices from dust.
- ▶ Check the outdoor unit at regular intervals. Contact customer service or an authorised service engineer if a fault occurs.

4.4.2 Maintenance after a long period of non-use

- ▶ Wipe the air inlet grille with a clean dry cloth so the indoor unit does not blow out dust.
- ▶ Make sure that the air inlet and air outlet are unobstructed and have not been inadvertently adjusted.
- ▶ Check all cables and connect the power supply.
- ▶ If required, make sure that the air filter is installed.

5 Troubleshooting

5.1 Faults with indication (Self diagnosis function)

If a fault occurs during operation, the LEDs flash for an extended period or an error code is displayed (e.g. EH 02).

If a fault is present for more than 10 minutes:

- ▶ Briefly disconnect the power supply and switch the indoor unit back on.

If a fault persists:

- ▶ Call customer service and provide the fault code and details of the appliance.

5.2 Faults not indicated

If faults occur during operation that cannot be eliminated:

- ▶ Call customer service about the fault, providing details of the device.

Fault	Possible cause
The output of the indoor unit is too low.	Temperature is set too high or too low.
	Air filter is soiled and must be cleaned.
	Unfavourable ambient conditions for the indoor unit, e.g. the ventilation openings of the devices are obstructed, doors/windows in the room are open or the room contains powerful heat sources.
	Low-noise operation is activated and prevents the full output from being used.
Indoor unit does not switch on.	The indoor unit has a safety mechanism to prevent overloading. It may take 3 minutes, until the indoor unit can be restarted.
	The batteries of the remote control are empty.
	The timer is switched on.
Operating mode changes from Cooling or Heating to Fan Mode.	The indoor unit changes operating mode to prevent the formation of frost.
	The set temperature is reached provisionally.
A white mist is coming from the indoor unit.	In humid regions, white mist may appear if there is a significant temperature difference between the indoor air and air-conditioned air.
White mist is emerging from the indoor unit and outdoor unit.	If heating mode is activated directly after automatic defrosting, this can generate white mist due to the higher level of humidity.
There is noise coming from the indoor unit and outdoor unit.	A swooshing noise may be heard inside the indoor unit if the position of the airflow grille is set back.
	A quiet hissing noise is normal during operation. This is caused by the flow of refrigerant.
	Creaks and squeaks may be heard, as the metal and plastic parts of the device expand or contract during heating/cooling.
	The outdoor unit also emits a range of other noises during operation which is normal.
Dust is being discharged from the indoor unit or outdoor unit.	Dust may accumulate in the devices if they are shut down for an extended period and not covered.
Unpleasant odour during operation.	Unpleasant odours in the air may enter the devices and spread.
	There may be mould on the air filter and it must therefore be cleaned.
The fan of the outdoor unit is not running continuously.	Variable fan control is used to ensure optimum operation.
Operation is irregular or unpredictable or the indoor unit is not responding.	The indoor unit may be affected by interference from mobile radio masts or external signal amplifiers.
	▶ Briefly disconnect the indoor unit from the power supply then restart it.
Air baffle or louvres do not run correctly.	Air baffle or louvres have been adjusted manually or have not been correctly installed.
	▶ Switch off the indoor unit and check whether the components are engaged correctly.
	▶ Power on the IDU.

Table 11

6 Environmental protection and disposal

Environmental protection is a fundamental corporate strategy of the Bosch Group.

The quality of our products, their economy and environmental safety are all of equal importance to us and all environmental protection legislation and regulations are strictly observed.

We use the best possible technology and materials for protecting the environment taking account of economic considerations.

Packaging

Where packaging is concerned, we participate in country-specific recycling processes that ensure optimum recycling.

All of our packaging materials are environmentally compatible and can be recycled.

Used appliances

Used appliances contain valuable materials that can be recycled.

The various assemblies can be easily dismantled. Synthetic materials are marked accordingly. Assemblies can therefore be sorted by composition and passed on for recycling or disposal.

Old electrical and electronic appliances



This symbol means that the product must not be disposed of with other waste, and instead must be taken to the waste collection points for treatment, collection, recycling and disposal.

The symbol is valid in countries where waste electrical and electronic equipment regulations apply, e.g. "European Directive 2012/19/EC on old electronic and electrical appliances". These regulations define the framework for the return and recycling of old electronic appliances that apply in each country.

As electronic devices may contain hazardous substances, it needs to be recycled responsibly in order to minimize any potential harm to the environment and human health. Furthermore, recycling of electronic scrap helps preserve natural resources.

For additional information on the environmentally compatible disposal of old electrical and electronic appliances, please contact the relevant local authorities, your household waste disposal service or the retailer where you purchased the product.

You can find more information here:
www.weee.bosch-thermotechnology.com/

Batteries

Batteries must not be disposed together with your household waste. Used batteries must be disposed of in local collection systems.

Refrigerant R32



The appliance contains fluorinated gas R32 (global warming potential 675¹⁾) mild combustibility and low toxicity (A2L or A2).

Contained quantity is indicated on the equipment outdoor unit name label.

Refrigerant is hazardous to the environment and must be collected and disposed of separately.

7 Data Protection Notice




We, **Bosch Thermotechnology Ltd., Cotswold Way, Warndon, Worcester WR4 9SW, United Kingdom** process product and installation information, technical and connection data, communication data, product registration and client history data to provide product functionality (art. 6 (1) sentence 1 (b)


GDPR), to fulfil our duty of product surveillance and for product safety and security reasons (art. 6 (1) sentence 1 (f) GDPR), to safeguard our rights in connection with warranty and product registration questions (art. 6 (1) sentence 1 (f) GDPR) and to analyze the distribution of our products and to provide individualized information and offers related to the product (art. 6 (1) sentence 1 (f) GDPR). To provide services such as sales and marketing services, contract management, payment handling, programming, data hosting and hotline services we can commission and transfer data to external service providers and/or Bosch affiliated enterprises. In some cases, but only if appropriate data protection is ensured, personal data might be transferred to recipients located outside of the European Economic Area. Further information are provided on request. You can contact our Data Protection Officer under: Data Protection Officer, Information Security and Privacy (C/ISP), Robert Bosch GmbH, Postfach 30 02 20, 70442 Stuttgart, GERMANY.

You have the right to object, on grounds relating to your particular situation or where personal data are processed for direct marketing purposes, at any time to processing of your personal data which is based on art. 6 (1) sentence 1 (f) GDPR. To exercise your rights, please contact us via privacy.ttgb@bosch.com To find further information, please follow the QR-Code.


1) Based on ANNEX I of REGULATION (EU) No 517/2014 of the European Parliament and of the Council of 16 April 2014.




1




4




2




5




3



6



7



8





Bosch Thermotechnik GmbH
Junkersstrasse 20-24
D-73249 Wernau

www.bosch-thermotechnology.com