




Greenstar 8000 Life & Style Installer guide

Style and substance



Greenstar 8000 Life **The big-time boiler**

For your customers and their busy family homes, the Greenstar 8000 Life can handle the most demanding heating requirements, without giving you a hard time with a complex installation or servicing schedule. With rear piping, pre-plumbing jig, and large condensate siphon – this is a heavyweight boiler with lightweight maintenance.









Why install the Greenstar 8000 Life?



Powerful

Outputs up to 50kW for combi or regular



Improved display

Easy and reliable pushbutton LCD display



Modern design

Clean and modern design for homes



Convenient

Optional Intelligent Filling
System can be added to combi



Easy installation

Installer-friendly servicing and maintenance



SimpleSwitch

With the CDi Classic for simpler installation

Greenstar 8000 Style **Top class boiler**

For the busiest mornings and the biggest family homes, the Greenstar 8000 Style sits sleek in your customer's homes with its contemporary, stunning design. A powerhouse able to cope with bustling schedules, but with rear piping and a pre-plumbing jig as standard – this is a boiler that can do it all, without taking up all of your time.









Why install the Greenstar 8000 Style?

All the features of the 8000 Life, plus:



Stunning design

Aesthetic design for contemporary homes available in black or white



Innovative display

Full colour display with backlit touch buttons



User friendly interface

Effortless interaction with a seamlessly designed interface

Style and substance



Top and side panels

- ► No further screws needed for internal access thanks to removable top and side panels
- ► With the casing removed, the boiler can be lifted easily with two large handles
- ► Its open structure allows for easy access to the hydraulic block



Front cover

- ► Reinforced steel front cover available in high gloss, black and white (Style only)
- ► Easy to remove with just one screw



Condensate trap and front access PRV

- ► The large capacity trap increases the volume of condensate discharge, reducing the risk of freezing
- Drain down the boiler without connecting to an external drain-off hose
- ► Front access PRV can be removed in less than 10 minutes



Pressure gauge and sensor

- Digital gauge featured on the boiler control display
- Pressure can be monitored during installation and maintenance even when the power is off
- ► High quality pressure sensor and pressure monitoring logic ensures no disruption



Control key

- Industry first 'RF Key' receiver links time and temperature controls to the boiler
- ► Enables you to fit our Greenstar Comfort+ II RF and Bosch EasyControl with ease



Hydraulic and wiring

- ► Control fascia can be quickly dropped for comfortable service access
- Wiring connections accessible without any screws, laid out similar to our Greenstar 4000
- ► Built-in screwdriver holder and screw tray for added convenience

04 Features 05

Greenstar 8000 Life & Style **Controls**



Bosch EasyControl

- Smart, internet connected programmable control
- ► Can be installed wirelessly with the Greenstar Lifestyle range
- ▶ DHW and CH can be programmed. monitored and controlled via the Bosch EasyControl app
- ▶ Decide heating times and temperatures for individual rooms with our smart Bosch TRVs*
- ► Store your details directly into the app, so your customer can contact you when they need to
- ► Smart integrations with Amazon Alexa, Siri shortcuts, and IFTTT
- ► Available in black or white so customers can match to their Style boiler



Comfort+ II RF

- Wireless room thermostat with backlit display, push-buttons and dial
- ► Load Compensation for enhanced efficiency
- ▶ Landlord function
- ▶ All-in-one time and temperature control - perfect for boilers that are not easily accessible
- ▶ Low pressure indication
- Six adjustable heating and hot water time periods using our easy to use menu
- ► Compatible with our Comfort+ Wireless Outdoor Weather Sensor



Comfort+ I RF (8000 Style only)

- ▶ Wireless room thermostat with clear display and simple dial adjustment
- ▶ Plug-and-play installation
- ▶ Pre-paired wireless room thermostat and RF kev receiver
- ▶ Load compensation for enhanced efficiency

Greenstar 8000 Life & Style The inside story

Separate combustion cover (not shown) allows other servicing steps to be completed without seal disturbance

10L Expansion Vessel

Fan delivers high outputs and a max flue length of up to 17m (60/100mm, horizontal)

Pressure gauge to support initial fill

Front-facing PRV for ease-of-access

Large volume siphon minimises likelihood of frozen condensate

Easy-to-remove side panels reduce lift weight

Combined drain-off and condensate supports straightforward boiler drain-down Keyless filling link (not shown) provides homeowners with a simple method of system pressure top-up

C5 Heat cell known for its robustness and high power, plus front-access for cleaning

Venturi design delivers up to 1:10 modulation, widening the operating range

Green touchpoints enhance intuitive component interaction



Life display 7-segment display with familiar status codes and




Style display Intuitive, clear colour display offers an easy-to-use menu structure solution for all


Range rating the max CH output (down to 50%) for smaller, wellinsulated properties

Greenstar 8000 Life & Style **Technical drawings**


Dimensions (mm)




Clearances (mm)



Maximum flue lengths (mm)





Greenstar 8000 Life & Style **Technical data**

Boiler type	Combi and Regular^			System			
Model	30kW	35kW	40kW	45kW	50kW	30kW	35kW
Maximum horizontal flue lengths (60/100)	17m	10m	11m	8m	9m	17m	10m
Maximum vertical flue lengths (60/100)	21m	14m	15m	12m	12m	21m	14m
Clearance above the appliance	170/210mm**	170/210mm**	170/210mm**	170/210mm**	170/210mm**	170/210mm**	170/210mm**
Clearance (sides)	5mm	5mm	5mm	5mm	5mm	5mm	5mm
Clearance (below)	200mm	200mm	200mm	200mm	200mm	200mm	200mm
Clearance (front)	450mm***	450mm***	450mm***	450mm***	450mm***	450mm***	450mm***
Width	440mm	440mm	440mm	440mm	440mm	440mm	440mm
Height	780mm	780mm	780mm	780mm	780mm	780mm	780mm
Depth	365mm	365mm	365mm	365mm	365mm	365mm	365mm
Combi flow rate at the hot water tap (35°C)	12.3 l/min^^	14.3 l/min^^	16.4 l/min^^	18.3 l/min^^	20.3 l/min^^		
Combi flow rate at the hot water tap (40°C)	11 l/min#	13 l/min#	14 l/min#	15 l/min#	18 l/min#		
Combi central heating output	3.0kW to 29.6kW	5.1kW to 33.7kW	5.1kW to 33.7kW	6.3kW to 33.8kW	6.3kW to 33.8kW		
ErP Space Heating Efficiency Class	A / 94%						
Combi ErP Water Heating Efficiency Class [†]	А	А	А	А	А		

^{**} Height for either 60/100 flue or 80/125 flue.

^{*** 20}mm from a removable cupboard door. 450mm from a fixed surface for servicing. Same clearances for ventilated and unventilated compartments.

[^] Regular variant available for the 8000 Life model only.

^{^^} Values for industry comparisons.

[#] Designed operational flow rate. Maximum flow is subject to a tolerance of 15%. Maximum flow rates will only be achieved if sufficient dynamic pressure between 2.3bar and 3.4 bar is available.

Declared load profile XL.

Greenstar 8000 Life & Style **Parts**

Greenstar 8000 Life

Combi	
Greenstar 8000 Life 30kW Combi (White) NG	7 738 100 800
Greenstar 8000 Life 35kW Combi (White) NG	7 738 100 801
Greenstar 8000 Life 40kW Combi (White) NG	7 738 100 802
Greenstar 8000 Life 45kW Combi (White) NG	7 738 100 803
Greenstar 8000 Life 50kW Combi (White) NG	7 738 100 804
Greenstar 8000 Life 30kW Combi (White) LPG	7 738 100 849
Greenstar 8000 Life 35kW Combi (White) LPG	7 738 100 850
Greenstar 8000 Life 40kW Combi (White) LPG	7 738 100 851
Greenstar 8000 Life 45kW Combi (White) LPG	7 738 100 852
Greenstar 8000 Life 50kW Combi (White) LPG	7 738 100 853

System	
Greenstar 8000 Life 30kW System (White) NG	7 738 100 807
Greenstar 8000 Life 35kW System (White) NG	7 738 100 808
Greenstar 8000 Life 30kW System (White) LPG	7 738 100 858
Greenstar 8000 Life 35kW System (White) LPG	7 738 100 859

Regular	
Greenstar 8000 Life 30kW Regular (White) NG	7 738 100 809
Greenstar 8000 Life 35kW Regular (White) NG	7 738 100 810
Greenstar 8000 Life 40kW Regular (White) NG	7 738 100 811
Greenstar 8000 Life 45kW Regular (White) NG	7 738 100 812
Greenstar 8000 Life 50kW Regular (White) NG	7 738 100 813
Greenstar 8000 Life 30kW Regular (White) LPG	7 738 100 860
Greenstar 8000 Life 35kW Regular (White) LPG	7 738 100 861
Greenstar 8000 Life 40kW Regular (White) LPG	7 738 100 862
Greenstar 8000 Life 45kW Regular (White) LPG	7 738 100 863
Greenstar 8000 Life 50kW Regular (White) LPG	7 738 100 864

Greenstar 8000 Style

Combi	
Greenstar 8000 Style 30kW Combi (Black) NG	7 738 100 832
Greenstar 8000 Style 35kW Combi (Black) NG	7 738 100 833
Greenstar 8000 Style 40kW Combi (Black) NG	7 738 100 834
Greenstar 8000 Style 45kW Combi (Black) NG	7 738 100 835
Greenstar 8000 Style 50kW Combi (Black) NG	7 738 100 836
Greenstar 8000 Style 30kW Combi (White) NG	7 738 100 795
Greenstar 8000 Style 35kW Combi (White) NG	7 738 100 796
Greenstar 8000 Style 40kW Combi (White) NG	7 738 100 797
Greenstar 8000 Style 45kW Combi (White) NG	7 738 100 798
Greenstar 8000 Style 50kW Combi (White) NG	7 738 100 799
Greenstar 8000 Style 30kW Combi (Black) LPG	7 738 100 844
Greenstar 8000 Style 35kW Combi (Black) LPG	7 738 100 845
Greenstar 8000 Style 40kW Combi (Black) LPG	7 738 100 846
Greenstar 8000 Style 45kW Combi (Black) LPG	7 738 100 847
Greenstar 8000 Style 50kW Combi (Black) LPG	7 738 100 848
Greenstar 8000 Style 30kW Combi (White) LPG	7 738 100 839
Greenstar 8000 Style 35kW Combi (White) LPG	7 738 100 840
Greenstar 8000 Style 40kW Combi (White) LPG	7 738 100 841
Greenstar 8000 Style 45kW Combi (White) LPG	7 738 100 842
Greenstar 8000 Style 50kW Combi (White) LPG	7 738 100 843

System	
Greenstar 8000 Style 30kW System (Black) NG	7 738 100 837
Greenstar 8000 Style 35kW System (Black) NG	7 738 100 838
Greenstar 8000 Style 30kW System (White) NG	7 738 100 805
Greenstar 8000 Style 35kW System (White) NG	7 738 100 806
Greenstar 8000 Style 30kW System (Black) LPG	7 738 100 856
Greenstar 8000 Style 35kW System (Black) LPG	7 738 100 857
Greenstar 8000 Style 30kW System (White) LPG	7 738 100 854
Greenstar 8000 Style 35kW System (White) LPG	7 738 100 855

Greenstar 8000 Life & Style Flues and accessories

100mm White Flues	
Standard telescopic flue & terminal (350 - 570mm)	7 716 191 082
Extension flue kit (960mm)	7 716 191 083
Short flue extension (220mm)	7 716 191 133
Plume management kit (60mm dia.)	7 716 191 086
90° flue bend	7 716 191 084
45° flue bend	7 716 191 085
Support bracket kit	7 716 191 177
Vertical 1,090mm BF kit (inc. adaptor)	7 719 002 430

100mm Silver Flues	
Silver Standard telescopic flue & terminal (350 – 570mm)	7 738 112 869
Silver Extension flue kit (960mm)	7 738 112 871
Silver Short flue extension (220mm)	7 738 112 873
Silver 90° flue bend x 1	7 738 112 874
Silver 45° flue bend x 2	7 738 112 875

Accessories	
Greenstar Intelligent Filling System	7 738 112 911
Greenstar System Filter (22mm mini)	7 733 600 266
Greenstar System Filter (22mm)	7 733 600 236
Greenstar System Filter (28mm)	7 733 600 237
Greenstar System Filter (22mm brass)	7 733 600 476
Vertical Pre-piping Assembly Kit	7 716 192 607
Greenstar Low Loss Header	7 716 192 614
DHW Pre-heat Accessory	7 738 113 072
Remote PRV Kit	7 738 112 910

System Care Packs	
Wireless Bosch EasyControl (White) System Care Pack	7 733 600 433
Wireless Bosch EasyControl (Black) System Care Pack	7 733 600 443
Greenstar Comfort+ I RF System Care Pack	7 733 600 400
Greenstar Comfort+ II RF System Care Pack	7 733 600 401
Greenstar Connected System Care Pack	7 733 601 377

Controls	
EasyControl (White)	7 736 701 341
EasyControl (Black)	7 736 701 392
EasyControl RF Key	7 738 113 610
EasyControl Table Stand	7 736 701 576
EasyControl and 3 x Smart TRV Set - White	7 736 701 555
EasyControl and 3 x Smart TRV Set - Black	7 736 701 556
Individual Smart TRV	7 736 701 575
Smart Individual Room Thermostat (230V)	8 750 001 003
Smart Individual Room Thermostat (24V)	8 750 001 004
Comfort+ (8000 Style only)	7 738 112 321
Comfort+ Stat RF	7 738 112 338
Comfort+ I RF (8000 Style only)	7 738 112 323
Comfort+ II RF	7 738 112 324
Greenstar Sense I	7 738 110 054
Greenstar Sense II	7 738 111 064
MT20 Mechanical Timer	7 733 600 332
MT20RF Mechanical Thermostat	7 733 600 333
Comfort+ Wireless Outdoor Weather Sensor	7 738 112 343

Unvented Cylinders	
Green Storage WB Range Unvented 90l	7 733 601 298
Green Storage WB Range Unvented 120l	7 733 601 299
Green Storage WB Range Unvented 150l	7 733 601 300
Green Storage WB Range Unvented 180l	7 733 601 301
Green Storage WB Range Unvented 210l	7 733 601 302
Green Storage WB Range Unvented 250l	7 733 601 303
Green Storage WB Range Unvented 300l	7 733 601 304
Green Storage WB Range Unvented Solar 180l	7 733 601 306
Green Storage WB Range Unvented Solar 210l	7 733 601 307
Green Storage WB Range Unvented Solar 250l	7 733 601 308
Green Storage WB Range Unvented Solar 300l	7 733 601 309

For additional controls and accessories, see our Gas & Oil Product Guide (8 716 122 882) for details. Flues and accessories 11

Get in touch

Sales

Tel: 0330 123 9669

Email: sales.bosch@uk.bosch.com

Technical Helpline (Pre & Post Sales)

Tel: 0330 123 3366

Email: technical-advice@uk.bosch.com

Spare Parts

Tel: 0330 123 9779

Email: spares.mailbox@uk.bosch.com

Controls Helpline

Tel: 0330 123 3641



Training

Tel: 0330 123 0166

Email: training@uk.bosch.com worcester-bosch.co.uk/eacademy

Worcester Bosch

Cotswold Way Warndon Worcester

WR4 9SW

worcester-bosch.co.uk

Calls to and from Bosch Thermotechnology Ltd may be recorded for training and quality assurance purposes. Worcester Bosch is a brand name of Bosch Thermotechnology Ltd. This brochure is accurate at the date of printing, but may be superseded and should be disregarded if specification and/or appearances are changed in the interest of continued improvement. The statutory rights of the consumer are not affected.

Share

We would love to see your installations!

- (f) Worcester Bosch Professional
- @WorcesterBoschProfessional
- (X) @WorcesterBosch
- (in) Worcester Bosch
- WorcesterBoschHeating

