

Technical data

MODEL		HEATSLAVE II EXTERNAL 12/18	HEATSLAVE II EXTERNAL 18/25	HEATSLAVE II EXTERNAL 25/32
Clearances*	Above	600mm	600mm	600mm
	Front	600mm	600mm	600mm
	RH/LH flue outlet on opposite side	10mm	10mm	10mm
	RH flue outlet on rear	85mm	85mm	85mm
	LH flue outlet on rear	10mm	10mm	10mm
	Rear - flue outlet on side	150mm	150mm	150mm
	Rear - rear flue outlet	2,500mm	2,500mm	2,500mm
Output kW to central heating (CH)		12kW - 18kW	18kW - 25kW	25kW - 32kW
Flow rate at the hot water tap (40°C)		15 l/min	18 l/min	22 I/min
ErP Seasonal space heating energy efficiency class		A / 90%	A / 90%	A / 91%
Optional plug-in timer		\checkmark	\checkmark	\checkmark

^{*}It is strongly recommended that the flue terminal faces away from walls to reduce the possibility of wetting occurring.

Control options




Accessories



Boiler dimensions

The Greenstar Heatslave II External's weather proof case features IP45 ingress protection.





Know your system

Combination, or 'combi' boilers, heat water directly from the mains when you turn on a tap, so you won't need a hot water storage cylinder or a cold water storage tank.